FEATURES & BENEFITS

- popular thin-walled heat-shrink conduits with good insulating properties, in 1 m long sections
- recommended for dry environment applications
- very wide range of sizes and colours



MECHANICAL DATA

Material	cross linked polyolefin
Recommended shrinking temperature [°C]	100 ÷ 125
Operating temperature [°C]	-30 ÷ +105
Shrinkage factor	2:1 4:1 for 4/1; 8/2 sizes

ELECTRICAL DATA

Breakdown strength [kV/mm]	12

DIMENSIONS

Length [m]	1

NOTE!

Coiled heat-shrink sleeves - on request

Type	Index Ergom	Colour	Inside diameter on delivery D [mm]	Inside diameter in full shrinkage d [mm]	Wall thickness on full shrinkage - s [mm]	Quantity in package [pcs]
TCR 1,6/0,8 BK (10 PCS)	E05ME-01010100203	black	1,6	0,8	0,43	10
TCR 1,6/0,8 BL (10 PCS)	E05ME-01010100403	blue	1,6	0,8	0,43	10
TCR 1,6/0,8 BR (10 PCS)	E05ME-01010100103	brown	1,6	0,8	0,43	10
TCR 1,6/0,8 CL (10 PCS)	E05ME-01010100903	transparent	1,6	0,8	0,43	10
TCR 1,6/0,8 GR (10 PCS)	E05ME-01010100503	green	1,6	0,8	0,43	10
TCR 1,6/0,8 RD (10 PCS)	E05ME-01010100303	red	1,6	0,8	0,43	10
TCR 1,6/0,8 VL (10 PCS)	E05ME-01010100603	violet	1,6	0,8	0,43	10
TCR 1,6/0,8 WT (10 PCS)	E05ME-01010100803	white	1,6	0,8	0,43	10
TCR 1,6/0,8 YL (10 PCS)	E05ME-01010100703	yellow	1,6	0,8	0,43	10
TCR 1,6/0,8 YL-GR (10 PCS)	E05ME-01010101003	yellow-green	1,6	0,8	0,43	10
TCR 2,4/1,2 BK (10 PCS)	E05ME-01010101203	black	2,4	1,2	0,51	10
TCR 2,4/1,2 BL (10 PCS)	E05ME-01010101403	blue	2,4	1,2	0,51	10
TCR 2,4/1,2 BR (10 PCS)	E05ME-01010101103	brown	2,4	1,2	0,51	10
TCR 2,4/1,2 CL (10 PCS)	E05ME-01010101903	transparent	2,4	1,2	0,51	10
TCR 2,4/1,2 GR (10 PCS)	E05ME-01010101503	green	2,4	1,2	0,51	10
TCR 2,4/1,2 RD (10 PCS)	E05ME-01010101303	red	2,4	1,2	0,51	10
TCR 2,4/1,2 VL (10 PCS)	E05ME-01010101603	violet	2,4	1,2	0,51	10
TCR 2,4/1,2 WT (10 PCS)	E05ME-01010101803	white	2,4	1,2	0,51	10
TCR 2,4/1,2 YL (10 PCS)	E05ME-01010101703	yellow	2,4	1,2	0,51	10
TCR 2,4/1,2 YL-GR (10 PCS)	E05ME-01010102003	yellow-green	2,4	1,2	0,51	10
TCR 3,2/1,6 BK (10 PCS)	E05ME-01010102203	black	3,2	1,6	0,51	10
TCR 3,2/1,6 BL (10 PCS)	E05ME-01010102403	blue	3,2	1,6	0,51	10
TCR 3,2/1,6 BR (10 PCS)	E05ME-01010102103	brown	3,2	1,6	0,51	10
TCR 3,2/1,6 CL (10 PCS)	E05ME-01010102903	transparent	3,2	1,6	0,51	10

Date of publication: 26/6/2020

Graphic project, pictures and all technical data and descriptions in this catalogue are protected by Polish and international copyright laws. Names and logos used in the content of this catalogue may be trademarks, for which ZAE Ergom Sp. z o.o. has exclusive protection rights. ZAE ERGOM reserves the right for changes in the assortment and parameters of its products.

Type	Index Ergom	Colour	Inside diameter on delivery D [mm]	Inside diameter in full shrinkage d [mm]	Wall thickness on full shrinkage - s [mm]	Quantity in package [pcs]
TCR 3,2/1,6 GR (10 PCS)	E05ME-01010102503	green	3,2	1,6	0,51	10
TCR 3,2/1,6 RD (10 PCS)	E05ME-01010102303	red	3,2	1,6	0,51	10
TCR 3,2/1,6 VL (10 PCS)	E05ME-01010102603	violet	3,2	1,6	0,51	10
TCR 3,2/1,6 WT (10 PCS)	E05ME-01010102803	white	3,2	1,6	0,51	10
TCR 3,2/1,6 YL (10 PCS)	E05ME-01010102703	yellow	3,2	1,6	0,51	10
TCR 3,2/1,6 YL-GR (10 PCS)	E05ME-01010103003	yellow-green	3,2	1,6	0,51	10
TCR 4/1 BK (10 PCS)	E05ME-01010103203	black	4,0	1,0	1,00	10
TCR 4/1 BL (10 PCS)	E05ME-01010103403	blue	4,0	1,0	1,00	10
TCR 4/1 BR (10 PCS)	E05ME-01010103103	brown	4,0	1,0	1,00	10
TCR 4/1 CL (10 PCS)	E05ME-01010103903	transparent	4,0	1,0	1,00	10
TCR 4/1 GR (10 PCS)	E05ME-01010103503	green	4,0	1,0	1,00	10
TCR 4/1 RD (10 PCS)	E05ME-01010103303	red	4,0	1,0	1,00	10
TCR 4/1 VL (10 PCS)	E05ME-01010103603	violet	4,0	1,0	1,00	10
TCR 4/1 WT (10 PCS)	E05ME-01010103803	white	4,0	1,0	1,00	10
TCR 4/1 YL (10 PCS)	E05ME-01010103703	yellow	4,0	1,0	1,00	10
TCR 4/1 YL-GR (10 PCS)	E05ME-01010104003	yellow-green	4,0	1,0	1,00	10
TCR 4,8/2,4 BK (10 PCS)	E05ME-01010104203	black	4,8	2,4	0,51	10
TCR 4,8/2,4 BL (10 PCS)	E05ME-01010104403	blue	4,8	2,4	0,51	10
TCR 4,8/2,4 BR (10 PCS)	E05ME-01010104103	brown	4,8	2,4	0,51	10
TCR 4,8/2,4 CL (10 PCS)	E05ME-01010104903	transparent	4,8	2,4	0,51	10
TCR 4,8/2,4 GR (10 PCS)	E05ME-01010104503	green	4,8	2,4	0,51	10
TCR 4,8/2,4 RD (10 PCS)	E05ME-01010104303	red	4,8	2,4	0,51	10
TCR 4,8/2,4 VL (10 PCS)	E05ME-01010104603	violet	4,8	2,4	0,51	10
TCR 4,8/2,4 WT (10 PCS)	E05ME-01010104803	white	4,8	2,4	0,51	10
TCR 4,8/2,4 YL (10 PCS)	E05ME-01010104703	yellow	4,8	2,4	0,51	10
TCR 4,8/2,4 YL-GR (10 PCS)	E05ME-01010105003	yellow-green	4,8	2,4	0,51	10
TCR 6,4/3,2 BK (10 PCS)	E05ME-01010105203	black	6,4	3,2	0,64	10
TCR 6,4/3,2 BL (10 PCS)	E05ME-01010105403	blue	6,4	3,2	0,64	10
TCR 6,4/3,2 BR (10 PCS)	E05ME-01010105103	brown	6,4	3,2	0,64	10
TCR 6,4/3,2 CL (10 PCS)	E05ME-01010105903	transparent	6,4	3,2	0,64	10
TCR 6,4/3,2 GR (10 PCS)	E05ME-01010105503	green	6,4	3,2	0,64	10
TCR 6,4/3,2 RD (10 PCS)	E05ME-01010105303	red	6,4	3,2	0,64	10
TCR 6,4/3,2 VL (10 PCS)	E05ME-01010105603	violet	6,4	3,2	0,64	10
TCR 6,4/3,2 WT (10 PCS)	E05ME-01010105803	white	6,4	3,2	0,64	10
TCR 6,4/3,2 YL (10 PCS)	E05ME-01010105703	yellow	6,4	3,2	0,64	10
TCR 6,4/3,2 YL-GR (10 PCS)	E05ME-01010106003	yellow-green	6,4	3,2	0,64	10
TCR 8/2 BK (10 PCS)	E05ME-01010106203	black	8,0	2,0	1,00	10
TCR 8/2 BL (10 PCS)	E05ME-01010106403	blue	8,0	2,0	1,00	10
TCR 8/2 BR (10 PCS)	E05ME-01010106103	brown	8,0	2,0	1,00	10
TCR 8/2 CL (10 PCS)	E05ME-01010106903	transparent	8,0	2,0	1,00	10
TCR 8/2 GR (10 PCS)	E05ME-01010106503	green	8,0	2,0	1,00	10
TCR 8/2 RD (10 PCS)	E05ME-01010106303	red	8,0	2,0	1,00	10
TCR 8/2 VL (10 PCS)	E05ME-01010106603	violet	8,0	2,0	1,00	10
TCR 8/2 WT (10 PCS)	E05ME-01010106803	white	8,0	2,0	1,00	10
TCR 8/2 YL (10 PCS)	E05ME-01010106703	yellow	8,0	2,0	1,00	10
TCR 8/2 YL-GR (10 PCS)	E05ME-01010107003	yellow-green	8,0	2,0	1,00	10
TCR 9,5/4,8 BK (10 PCS)	E05ME-01010107203	black	9,5	4,8	0,64	10
TCR 9,5/4,8 BL (10 PCS)	E05ME-01010107403	blue	9,5	4,8	0,64	10
TCR 9,5/4,8 BR (10 PCS)	E05ME-01010107103	brown	9,5	4,8	0,64	10
TCR 9,5/4,8 CL (10 PCS)	E05ME-01010107903	transparent	9,5	4,8	0,64	10
TCR 9,5/4,8 GR (10 PCS)	E05ME-01010107503	green	9,5	4,8	0,64	10
TCR 9,5/4,8 RD (10 PCS)	E05ME-01010107303	red	9,5	4,8	0,64	10
TCR 9,5/4,8 VL (10 PCS)	E05ME-01010107603	violet	9,5	4,8	0,64	10
TCR 9,5/4,8 WT (10 PCS)	E05ME-01010107803	white	9,5	4,8	0,64	10
TCR 9,5/4,8 YL (10 PCS)	E05ME-01010107703	yellow	9,5	4,8	0,64	10
TCR 9,5/4,8 YL-GR (10 PCS)	E05ME-01010108003	yellow-green	9,5	4,8	0,64	10
TCR 12,7/6,4 BK (10 PCS)	E05ME-01010108203	black	12,7	6,4	0,64	10
TCR 12,7/6,4 BL (10 PCS)	E05ME-01010108403	blue	12,7	6,4	0,64	10
TCR 12,7/6,4 BR (10 PCS)	E05ME-01010108103	brown	12,7	6,4	0,64	10
TCR 12,7/6,4 CL (10 PCS)	E05ME-01010108903	transparent	12,7	6,4	0,64	10
TCR 12,7/6,4 GR (10 PCS)	E05ME-01010108503	green	12,7	6,4	0,64	10
TCR 12,7/6,4 RD (10 PCS)	E05ME-01010108303	red	12,7	6,4	0,64	10

Date of publication: 26/6/2020

Graphic project, pictures and all technical data and descriptions in this catalogue are protected by Polish and international copyright laws.
Names and logos used in the content of this catalogue may be trademarks, for which ZAE Ergom Sp. z o.o. has exclusive protection rights.
ZAE ERGOM reserves the right for changes in the assortment and parameters of its products.

Type	Index Ergom	Colour	Inside diameter on delivery D [mm]	Inside diameter in full shrinkage d [mm]	Wall thickness on full shrinkage - s [mm]	Quantity in package [pcs]
TCR 12,7/6,4 VL (10 PCS)	E05ME-01010108603	violet	12,7	6,4	0,64	10
TCR 12,7/6,4 WT (10 PCS)	E05ME-01010108803	white	12,7	6,4	0,64	10
TCR 12,7/6,4 YL (10 PCS)	E05ME-01010108703	yellow	12,7	6,4	0,64	10
TCR 12,7/6,4 YL-GR (10 PCS)	E05ME-01010109003	yellow-green	12,7	6,4	0,64	10
TCR 19/9,5 BK (5 PCS)	E05ME-01010109203	black	19,0	9,5	0,76	5
TCR 19/9,5 BL (5 PCS)	E05ME-01010109403	blue	19,0	9,5	0,76	5
TCR 19/9,5 BR (5 PCS)	E05ME-01010109103	brown	19,0	9,5	0,76	5
TCR 19/9,5 CL (5 PCS)	E05ME-01010109903	transparent	19,0	9,5	0,76	5
TCR 19/9,5 GR (5 PCS)	E05ME-01010109503	green	19,0	9,5	0,76	5
TCR 19/9,5 RD (5 PCS)	E05ME-01010109303	red	19,0	9,5	0,76	5
TCR 19/9,5 VL (5 PCS)	E05ME-01010109603	violet	19,0	9,5	0,76	5
TCR 19/9,5 WT (5 PCS)	E05ME-01010109803	white	19,0	9,5	0,76	5
TCR 19/9,5 YL (5 PCS)	E05ME-01010109703	yellow	19,0	9,5	0,76	5
TCR 19/9,5 YL-GR (5 PCS)	E05ME-01010110003	yellow-green	19,0	9,5	0,76	5
TCR 25,4/12,7 BK (5 PCS)	E05ME-01010110203	black	25,4	12,7	0,89	5
TCR 25,4/12,7 BL (5 PCS)	E05ME-01010110403	blue	25,4	12,7	0,89	5
TCR 25,4/12,7 BR (5 PCS)	E05ME-01010110103	brown	25,4	12,7	0,89	5
TCR 25,4/12,7 CL (5 PCS)	E05ME-01010110903	transparent	25,4	12,7	0,89	5
TCR 25,4/12,7 GR (5 PCS)	E05ME-01010110503	green	25,4	12,7	0,89	5
TCR 25,4/12,7 RD (5 PCS)	E05ME-01010110303	red	25,4	12,7	0,89	5
TCR 25,4/12,7 VL (5 PCS)	E05ME-01010110603	violet	25,4	12,7	0,89	5
TCR 25,4/12,7 WT (5 PCS)	E05ME-01010110803	white	25,4	12,7	0,89	5
TCR 25,4/12,7 YL (5 PCS)	E05ME-01010110703	yellow	25,4	12,7	0,89	5
TCR 25,4/12,7 YL-GR (5 PCS)	E05ME-01010111003	yellow-green	25,4	12,7	0,89	5
TCR 38/19 BK (5 PCS)	E05ME-01010111203	black	38,0	19,0	1,02	5
TCR 38/19 BL (5 PCS)	E05ME-01010111403	blue	38,0	19,0	1,02	5
TCR 38/19 BR (5 PCS)	E05ME-01010111103	brown	38,0	19,0	1,02	5
TCR 38/19 CL (5 PCS)	E05ME-01010111903	transparent	38,0	19,0	1,02	5
TCR 38/19 GR (5 PCS)	E05ME-01010111503	green	38,0	19,0	1,02	5
TCR 38/19 RD (5 PCS)	E05ME-01010111303	red	38,0	19,0	1,02	5
TCR 38/19 VL (5 PCS)	E05ME-01010111603	violet	38,0	19,0	1,02	5
TCR 38/19 WT (5 PCS)	E05ME-01010111803	white	38,0	19,0	1,02	5
TCR 38/19 YL (5 PCS)	E05ME-01010111703	yellow	38,0	19,0	1,02	5
TCR 38/19 YL-GR (5 PCS)	E05ME-01010112003	yellow-green	38,0	19,0	1,02	5
TCR 51/25,5 BK (5 PCS)	E05ME-01010112103	black	51,0	25,5	1,14	5
TCR 51/25,5 BL (5 PCS)	E05ME-01010112803	blue	51,0	25,5	1,14	5
TCR 51/25,5 CL (5 PCS)	E05ME-01010112603	transparent	51,0	25,5	1,14	5
TCR 51/25,5 GR (5 PCS)	E05ME-01010112503	green	51,0	25,5	1,14	5
TCR 51/25,5 RD (5 PCS)	E05ME-01010112403	red	51,0	25,5	1,14	5
TCR 51/25,5 YL (5 PCS)	E05ME-01010112703	yellow	51,0	25,5	1,14	5
TCR 76/38 BK (5 PCS)	E05ME-01010112203	black	76,0	38,0	1,27	5
TCR 76/38 BL (5 PCS)	E05ME-01010113103	blue	76,0	38,0	1,27	5
TCR 76/38 CL (5 PCS)	E05ME-01010113303	transparent	76,0	38,0	1,27	5
TCR 102/51 BK (5 PCS)	E05ME-01010112303	black	102,0	51,0	1,40	5

Date of publication: 26/6/2020

Graphic project, pictures and all technical data and descriptions in this catalogue are protected by Polish and international copyright laws.
Names and logos used in the content of this catalogue may be trademarks, for which ZAE Ergom Sp. z o.o. has exclusive protection rights.
ZAE ERGOM reserves the right for changes in the assortment and parameters of its products.